


Bismarck Series Pendant






Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
• W 12 • HT 25 • OAH 72 (OverAll Height)	FJE	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA AG	ST SP	SQ
BM1326L • W 15 • HT 27	GHI	15,600lm LED (88W)	7,100lm LED (51W)	2	PC	WA AG	ST SP	SQ
• HI 27 • OAH 96 (OverAll Height)	GHP	19,800lm LED (124W)	12,500lm LED (93W)	2	PC	WA AG	ST SP	SQ
	FJF	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA AG	ST SP	SQ
• W 15 • HT 32 • OAH 96 (OverAll Height)	GKY	15,600lm LED (88W)	7,100lm LED (51W)	2	PC	WA AG	ST SP	SQ
	DMR	24,000lm LED (150W)	12,500lm LED (93W)	2	PC	WA AG	ST SP	SQ
	FJG	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA AG	ST SP	SQ
BM1436L • W 16 • HT 37	DHH	24,600lm LED (141W)	12,500lm LED (93W)	2	PC	WA AG	ST SP	SQ
• OAH 96 (OverAll Height)	GEJ	30,900lm LED (176W)	12,500lm LED (93W)	2	PC	WA AG	ST SP	SQ
	FJH	9-60W A19 (540W)	1-100W PAR38 (100W)	3	PC	WA AG	ST SP	SQ

BM1842L	DNJ	39,400lm LED (229W)	12,500lm LED (93W)	2	PC	WA AG	ST SP	SQ
• W 21 • HT 44								
• OAH 120 (OverAll Height)	FJI	12-MAX 45W LED Med. Base (540W)	1-100W A21 (100W)	2	PC	WA AG	ST SP	SQ

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- · Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

l a	m	n	S

60W A19 Medium Base, 60W Max, Incandesent or LED
100W PAR38 Medium Base, 100W Max, Incandesent or LED

MAX 45W LED 45W-LED A21, medium base

Med. Base

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser
AG Premium Glass Diffuser

Mountings

ST Stem

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

0 D1 1 D2 2 D3