

Cleveland Series Wall Bracket



| Model Number | Lamping Code | Body Lamping      | Circuit | Finish | Diffuser | Mounting | Louver | Options |
|--------------|--------------|-------------------|---------|--------|----------|----------|--------|---------|
| CL0816B      | AHZ          | 1-100W A21 (100W) | 1       | PC     | WA       | WM       | SQ     | BL      |
|              | • W 8"       |                   |         |        |          |          |        |         |
|              | • HT 16"     |                   |         |        |          |          |        |         |
|              | • EXT 11"    |                   |         |        |          |          |        |         |
| CL1020B      | DEM          | 3,900lm LED (24W) | 1       | PC     | WA       | WM       | SQ     | BL      |
|              | AIB          | 1-100W A21 (100W) | 1       | PC     | WA       | WM       | SQ     | BL      |
|              | • W 10"      |                   |         |        |          |          |        |         |
|              | • HT 20"     |                   |         |        |          |          |        |         |
| CL1224B      | FFX          | 5,400lm LED (33W) | 1       | PC     | WA       | WM       | SQ     | BL      |
|              | GBW          | 2-100W A21 (200W) | 1       | PC     | WA       | WM       | SQ     | BL      |
|              | • W 12"      |                   |         |        |          |          |        |         |
|              | • HT 24"     |                   |         |        |          |          |        |         |
|              | • EXT 15"    |                   |         |        |          |          |        |         |

| SAMPLE CATALOG NUMBER                                                |
|----------------------------------------------------------------------|
| Model Number - Lamping Code - Finish - Mounting - Diffuser - Options |

Scale

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)

Abbreviation Key

Lamps

100W A21      Medium Base, 100W Max, Incandesent or LED

Finish Types

PC      Powder Coat

Diffuser Types

WA      Standard Acrylic Diffuser

Mountings

WM      Wall Mount

- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

| Louvers       |             |
|---------------|-------------|
| SQ            | Square Cell |
|               |             |
| Dimming Types |             |
| 0             | D1          |
| 2             | D3          |
|               |             |
| Options       |             |
| BL            | Bottom Lens |