



Corvallis Series Ceiling Mount



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver
CV1008C	AST	2-100W A21 (200W)	1	PC	WA	CC	SQ
• W 10" • HT 11"							
CV1209C	GJL	5,400lm LED (33W)	1	PC	WA	CC	SQ
• W 12" • HT 12"							
	ASV	3-100W A21 (300W)	1	PC	WA	CC	SQ

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver

Abbreviation Key	
Lamps	
100W A21	Medium Base, 100W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
Mountings	
CC	Ceiling Canopy
Louvers	
SQ	Square Cell
Dimming Types	

• Wired for single circuit operation, Body Lamping	0	D1
• Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability	1	D2
• Standard LED CRI is 80 - contact us for alternate CRI availability		
• Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.		
• Standard LED dimming is 0-10v		
• Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility		
• Mounts to standard electrical junction box (by others)		
• UL / cUL or ETL / cETL listed		
• Contact Us for more lamping options.		