
# Craft Metal Products Inc.

# **Corvallis Series Pendant**





Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
CV1024L • W 12 • HT 25 • OAH 72	GEK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ


• OAH 72 (OverAll Height)

CV1226L	DVI	14,500lm LED (86W)	5,100lm LED (36W)	2	PC	WA	ST CH	SQ
• W 15 • HT 27 • OAH 96							SM SP	
(OverAll Height)	DOC	14,500lm LED(86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ
	DOD	14,500lm LED(86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	DOF	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	FJC	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ
<b>CV1231L</b> • W 15 • HT 32 • OAH 96 (OverAll Height)	EFJ	14,500lm LED(86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ
	DOT	14,500lm LED(86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	DMJ	23,100lm LED (146W)	12,500lm LED(93W)	2	PC	WA	ST CH SM SP	SQ
	DLP	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ

	FJD	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ
CV1236L • W 12" • HT 36" • OAH 96" (OverAll Height)	GLF	15,400lm LED(86W)	5,100lm LED(33W)	2	PC	WA	ST CH SM SP	SQ
	GJF	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	GKI	33,700lm LED (224W)	12,500lm LED(93W)	2	PC	WA	ST CH SM SP	SQ
	GIY	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ

#### SAMPLE CATALOG NUMBER

### Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



## PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- · Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

# Abbreviation Key

Lamps	
60W A19	Medium Base, 60W Max, Incandesent or LED
100W PAR38	Medium Base, 100W Max, Incandesent or LED
100W PAR38	Medium Base, 100W Max, Incandesent or LED

# **Finish Types**

PC Powder Coat

### Diffuser Types

#### WA Standard Acrylic Diffuser

Mountings	
ST	Stem
СН	Chain
SM	Surface Mount Chain
SP	Steep Pitch Canopy for Stem

# Louvers SQ

Square Cell

Dimming Types						
0	D1					
1	D2					
2	D3					