

Corvallis Series Wall Sconce



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
CV0816S • W 8 • HT 17 • EXT 5	DYX	1,000lm LED (7W)	1	PC	WA	WM	BD	BL
	DYY	1,800lm LED (14W)	1	PC	WA	WM	BD	BL
	ASX	1-60W A19 (60W)	1	PC	WA	WM	BD	BL
CV1020S • W 10 • HT 21 • EXT 6	DYZ	1,800lm LED (14W)	1	PC	WA	WM	BD	BL
	DZA	3,100lm LED (22W)	1	PC	WA	WM	BD	BL
	ASZ	2-100W A21 (200W)	1	PC	WA	WM	BD	BL
CV1224S • W 12 • HT 25 • EXT 7	DZB	6,300lm LED (40W)	1	PC	WA	WM	BD	BL
	FEH	7,100lm LED (44W)	1	PC	WA	WM	BD	BL
	ATC	3-100W A21 (300W)	1	PC	WA	WM	BD	BL

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

Abbreviation Key

Lamps

60W A19Medium Base, 60W Max, Incandesent or LED

100W A21Medium Base, 100W Max, Incandesent or LED

Finish Types

PCPowder Coat

Diffuser Types

WASandard Acrylic Diffuser

Mountings

WMWall Mount

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)

- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Louvers

BD Bottom Perf Door

Dimming Types

0 D1
1 D2

Options

BL Bottom Lens
BD Bottom Door