
Easton Series 3-Arm Cluster Pendant





Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
EA2724U	GCB	12-60W A19 (720W)	3-100W A19 (300W)	2	PC	WA AG	ST SP	SQ
• W 37						AG	JF	

• W 37 • HT 33

• OAH 96

(OverAll Height)

• Y 3 @ 12"x27"

EA3026U	DQK	43,600lm LED (258W)	21,400lm LED (152W)	2	PC	WA AG	ST SP	SQ
• W 42 • HT 35 • OAH 96								
• OAH 96 (OverAll Height) • Y 3 @ 14"x29"	DQM	69,300lm LED (436W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ
	FKW	18-60W A19 (1080W)	3-100W A21 (300W)	2	PC	WA AG	ST SP	SQ
EA3931U	DQN	43,600lm LED (258W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ
• W 53 • HT 40								
 OAH 120 (OverAll Height) Y 3 @ 16"x35" 	DQO	69,300lm LED (436W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ
	DQP	88,700lm LED (575W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ
	FKX	18-60W A19 (1080W)	3-100W A21 (300W)	2	PC	WA AG	ST SP	SQ
EA4836U	GAB	53,600lm LED (298W)	15,500lm LED(108W)	2	PC	WA AG	ST SP	SQ
• W 63								

• W 63

• HT 45

• OAH 120


(OverAll Height)

• Y 3 @ 18"x40"

GAC	53,600lm LED (298W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ
FYV	74,800lm LED (436W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ
FYW	105,900lm LED (713W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ
FKY	27-60W A19 (1620W)	3-100W A21 (300W)	3	PC	WA AG	ST SP	SQ

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- · Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- · Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- · Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- · For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps	
60W A19	Medium Base, 60W Max, Incandesent or LED
100W A19	Medium Base, 100W Max, Incandesent or LED

Finish Types

Diffuser Types	
WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings Stem

ST	Stem
SP	Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming	Types		
0	D1		
1	D2		
2	D3		