
Easton Series 6-Arm Satellite Pendant





Model Number	Lamping Code	Body Lamping	Satellite Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
EA4836A • W 48 • HT 39 • OAH 96 (OverAll Height) • X 1 @ 14"x39" • Y 6 @ 10"x22"	EIB	5-60W A19 (300W)	12-60W A19 (720W)	1-26W PAR38 LED (26W)	3	PC	WA AG	ST CH TC SP	SQ

EA6045A	EIC	9-60W A19 (540W)	12-60W A19 (720W)	1-26W PAR38 LED (26W)	3	PC	WA AG	ST CH	SQ
W 60								TC	
HT 49 OAH 120								SP	
(OverAll Height)									
X 1 @ 16"x49"									
Y 6 @ 12"x27"									

EA7254A	EID	12-60W A19 (720W)	12-60W A19 (720W)	1-26W PAR38 LED (26W)	3	PC	WA AG	ST CH	SQ
• W 72								TC	
• HT 58 • OAH 120								SP	
(OverAll Height)									

• X 1 @ 18"x58" • Y 6 @ 14"x29"

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED 26W PAR38 Medium Base, 26W Max, LED LED



CEILING HEIGHT: 15' DOOR HEIGHT: 7' SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- · Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available Energy efficient LED lamping
 High power factor electronic LED driver
- Wired for three circuit operation, Body Lamping, Down Lamping and Satellite
- Lamping

 Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
 Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
 Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)For slopes greater than 35 degrees (from horizontal) order steep pitch adapter
- (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser
Mountings	
ST	Stem
СН	Chain
тс	Triple Chain Spreader
SP	Steep Pitch Canopy for Stem

Louvers

Square Cell

SQ