
Craft Metal Products Inc.

Hartford Series Pendant






Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
HF1224L • W 12 • HT 26 • OAH 72 (OverAll Height)	GBL	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO

HF1426L	DVG	14,500lm LED (86W)	5,100lm LED (36W)	2	PC	WA AG	ST CH	SQ	CUT LOGO
• W 14 • HT 29 • OAH 96						AG	TC SM SP		LUGU
(OverAll Height)	DFB	14,500lm LED(86W)	7,100lm LED(51W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
	DTG	14,500lm LED(86W)	12,500lm LED (93W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
	EOB	23,100lm LED(146W)	7,100lm LED(51W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
	DFJ	23,100lm LED(146W)	12,500lm LED(93W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
	FIH	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
HF1631L • W 16 • HT 34 • OAH 96	DFA	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
(OverAll Height)	DLX	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA AG	ST CH TC	SQ	CUT LOGO

							SM SP		
	DCR	29,500lm LED(192W)	12,500lm LED(93W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
	FII	6-60W A19(360W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
HF1836L • W 18 • HT 40 • OAH 120	FYJ	24,900lm LED(146W)	12,500lm LED(93W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
(OverAll Height)	FIJ	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
HF2242L • W 22 • HT 46 • OAH 120	GGO	31,000lm LED(185W)	12,500lm LED(93W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO
(OverAll Height)	FIL	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH TC SM SP	SQ	CUT LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- · Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- · Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver •
- Wired for dual circuit operation, Body Lamping and Down Lamping • Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- · Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- · For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- · Contact Us for more lamping options.

Abbreviation Key

Medium Base, 60W Max, Incandesent or LED
Medium base, 00W Max, incandesent of LED
Medium Base. 100W Max. Incandesent or LED

Finish Types PC

Powder Coat

Diffuser Types	
WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings	
ST	Stem
СН	Chain
ТС	Triple Chain Spreader
SM	Surface Mount Chain
SP	Steep Pitch Canopy for Stem

Louvers Square Cell

Dimming Types						
0	D3					
1	D1					
2	D2					
3	D16					

Options CUT

SQ

Cut-Out Symbol

LOGO Custom Logo