
Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

# Houston Series 3-Arm Cluster Pendant







| Model Number | Lamping Code | Body Lamping | Down Lamping | Circuit | Finish | Diffuser | Mounting | Louver | Options |
|---|---|---|---|---|---|---|---|---|---|
| **HO2724U**<br>• W 37<br>• HT 32<br>• OAH 96 (OverAll Height)<br>• Y 3 @ 12"x24" | GCB | 12-60W A19 (720W) | 3-100W A19 (300W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| **HO3026U**<br>• W 42"<br>• HT 34"<br>• OAH 96" (OverAll Height)<br>• Y 3 @ 14"x26" | DQK | 43,600lm LED (258W) | 21,400lm LED (152W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | DQM | 69,300lm LED (436W) | 37,600lm LED (278W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | FKW | 18-60W A19 (1080W) | 3-100W A21 (300W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| **HO3931U**<br>• W 53<br>• HT 39<br>• OAH 120 (OverAll Height)<br>• Y 3 @ 16"x31" | DQN | 43,600lm LED (258W) | 37,600lm LED (278W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | DQO | 69,300lm LED (436W) | 37,600lm LED (278W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | DQP | 88,700lm LED (575W) | 37,600lm LED (278W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | FKX | 18-60W A19 (1080W) | 3-100W A21 (300W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| **HO4836U**<br>• W 63<br>• HT 44<br>• OAH 120 (OverAll Height)<br>• Y 3 @ 18"x36" | GAB | 53,600lm LED (298W) | 15,500lm LED (108W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | GAC | 53,600lm LED (298W) | 37,600lm LED (278W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | FYV | 74,800lm LED (436W) | 37,600lm LED (278W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | FYW | 105,900lm LED (713W) | 37,600lm LED (278W) | 2 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |
| | FKY | 27-60W A19 (1620W) | 3-100W A21 (300W) | 3 | PC | WA<br>AG | ST<br>SP | SQ | SIL<br>LOGO |

SAMPLE CATALOG NUMBER

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

## Scale




**PRODUCT FEATURES**

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

## Abbreviation Key

### Lamps

| | |
|---|---|
| 60W A19 | Medium Base, 60W Max, Incandesent or LED |
| 100W A19 | Medium Base, 100W Max, Incandesent or LED |

### Finish Types

| | |
|---|---|
| PC | Powder Coat |

### Diffuser Types

| | |
|---|---|
| WA | Standard Acrylic Diffuser |
| AG | Premium Glass Diffuser |

### Mountings

| | |
|---|---|
| ST | Stem |
| SP | Steep Pitch Canopy for Stem |

### Louvers

| | |
|---|---|
| SQ | Square Cell |

### Dimming Types

| | |
|---|---|
| 0 | D2 |
| 1 | D3 |
| 2 | D1 |

### Options

| | |
|---|---|
| SIL | Silhouette Symbol |
| LOGO | Custom Logo |