


## Norwich Series Ceiling Mount



**SAMPLE CATALOG NUMBER**  
Model Number - Lamping Code - Finish - Hanging - Diffuser - Options

Model	Lamping Options		Voltage	Circuit	Finish	Louver	Hanging	Diffuser	Options	Dimensions	
Model Number	Lamping Code	Body Lamping								W	HT
NW1207C	AMZ	2-F32TBX (77W)	120/277	1	PC	CR	CC	AD	DM	W	12"
	AMY	2-100A19 (200W)	120	1		SQ		AG		HT	11"
								GA		OAH	N/A
NW1408C	ANB	2-F42TBX (99W)	120/277	1	PC	CR	CC	AD	DM	W	14"
	ANA	3-100A19 (300W)	120	1		SQ		AG		HT	13"
								GA		OAH	N/A
NW1609C	AND	3-F42TBX (148W)	120/277	1	PC	CR	CC	AD	DM	W	16"
	ANC	3-150A21 (450W)	120	1		SQ		AG		HT	14"
								GA		OAH	N/A
NW1811C	ANF	4-F42TBX (197W)	120/277	1	PC	CR	CC	AD	DM	W	18"
	ANE	3-150A21 (450W)	120	1		SQ		AG		HT	17"
								GA		OAH	N/A

### PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic ballast or LED driver
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Mounts to standard 4" octagonal electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

### Abbreviation Key

#### Dimensions

W	Width
HT	Height
OAH	Overall Height

#### Lamp Descriptions

100A19	100W A19, medium base
150A21	150W A21, medium base
F32TBX	32W triple biax, 4-PIN GX24q-3 base
F42TBX	42W triple biax, 4-PIN GX24q-4 base

#### Finishes

PC	Powder Coat
----	-------------

#### Hanging Style

CC Ceiling Canopy

Diffusers

AD Acrylic (White Acrylic Standard)

AG Art Glass

GA Glass Alternative

Options

DM Dimming

Louver

CR CONCENTRIC RING (Not available on LED lamping)

SQ SQUARE CELL (Must be used on all LED lamping)