


Phoenix Series Pendant






Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
PX1024L • W 10" • HT 24" • OAH 72" (OverAll Height)	GEK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
PX1226L	DVI	14,500lm LED (86W)	5,100lm LED (36W)	2	PC	WA	ST	SQ	CUT
• W 12" • HT 26" • OAH 96" (OverAll Height)							CH SM SP		LOGO
	DOC	14,500lm LED(86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DOD	14,500lm LED(86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DOF	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	FJC	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
• W 12" • HT 31" • OAH 96" (OverAll Height)	EFJ	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DOT	14,500lm LED(86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DMJ	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	DLP	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	FJD	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST	SQ	CUT

							CH SM SP		LOGO
PX1236L • W 12" • HT 36" • OAH 96" (OverAll Height)	GLF	15,400lm LED (86W)	5,100lm LED (33W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	GJF	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	GKI	33,700lm LED (224W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO
	GIY	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ	CUT LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- · Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED
100W PAR38 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

ST Stem
CH Chain
SM Surface Mount Chain
SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

0 D1 1 D2 2 D3

Options

CUT Cut-Out Symbol LOGO Custom Logo