Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

Rockford Series Wall Sconce






Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
RF0816S • W 8" • HT 16" • EXT 4"	DYW	1,000lm LED (7W)	1	PC	WA	WM	BD	SIL BL
	DYK	1,800lm LED (14W)	1	PC	WA	WM	BD	SIL BL
	AHS	1-60W A19 (60W)	1	PC	WA	WM	BD	SIL BL
RF1020S • W 10" • HT 20" • EXT 5"	DYL	1,800lm LED (14W)	1	PC	WA	WM	BD	SIL BL
	DYM	3,100lm LED (22W)	1	PC	WA	WM	BD	SIL BL
	AHU	2-100W A21 (200W)	1	PC	WA	WM	BD	SIL BL
RF1224S • W 12" • HT 24" • EXT 6"	DYO	6,300lm LED (40W)	1	PC	WA	WM	BD	SIL BL
	DYN	7,100lm LED (44W)	1	PC	WA	WM	BD	SIL BL
	AHX	3-100W A21 (300W)	1	PC	WA	WM	BD	SIL BL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing

Abbreviation Key

Lamps

60W A19	Medium Base, 60W Max, Incandesent or LED
100W A21	Medium Base, 100W Max, Incandesent or LED

Finish Types

PC	Powder Coat

Diffuser Types

WA	Standard Acrylic Diffuser

Mountings

- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

WM	Wall Mount

Louvers	
BD	Bottom Perf Door

Dimming Types	
0	D1
1	D2
2	D3

Options	
SIL	Silhouette Symbol
BL	Bottom Lens
BD	Bottom Door