


Riverside Series Ceiling Mount



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Diffuser Accent	Mounting	Louver	Options
RS1007C	AHO	2-100W A21 (200W)	1	PC	WA	DAC CDA	CC	SQ	SIL LOGO
• W 11 • HT 10									
RS1208C	GJJ	5,400lm LED (33W)	1	PC	WA	DAC CDA	CC	SQ	SIL LOGO
• W 13 • HT 11									
	AHQ	3-100W A21 (300W)	1	PC	WA	DAC CDA	CC	SQ	SIL LOGO

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'

DOOR HEIGHT: 7'

SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer

Abbreviation Key	
Lamps	
100W A21	Medium Base, 100W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
Diffuser Accent Types	
DAC	Diffuser Accent Color
CDA	Custom Diffuser Accent
Mountings	
CC	Ceiling Canopy
Louvers	
SQ	Square Cell

- manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Dimming Types

0	D1
1	D2

Options

SIL	Silhouette Symbol
LOGO	Custom Logo