

Riverside Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Diffuser Accent	Mounting	Louver	Options
RS0816B	AHZ	1-100W A21 (100W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
	• W 8"								
	• HT 16"								
	• EXT 11"								
RS1020B	DEM	3,900lm LED (24W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
	• W 10"								
	• HT 20"								
	• EXT 13"								
RS1224B	AIB	1-100W A21 (100W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
	FFX	5,400lm LED (33W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
	• W 12"								
	• HT 24"								
	• EXT 15"								
	GBW	2-100W A21 (200W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Diffuser Accent Types

DAC Diffuser Accent Color

CDA Custom Diffuser Accent

- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Mountings	
WM	Wall Mount
Louvers	
SQ	Square Cell
Dimming Types	
0	D1
2	D3
Options	
SIL	Silhouette Symbol
LOGO	Custom Logo
BL	Bottom Lens