Riverside Series Wall Bracket






Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Diffuser Accent	Mounting	Louver	Options
RS0816B • W 8" • HT 16" • EXT 11"	AHZ	1-100W A21 (100W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
RS1020B • W 10" • HT 20" • EXT 13"	DEM	3,900lm LED (24W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
	AIB	1-100W A21 (100W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
RS1224B • W 12" • HT 24" • EXT 15"	FFX	5,400lm LED (33W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL
	GBW	2-100W A21 (200W)	1	PC	WA	DAC CDA	WM	SQ	SIL LOGO BL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)

Abbreviation Key

Lamps 100W A21 Medium Base, 100W Max, Incandesent or LED Finish Types PC Powder Coat Diffuser Types WA Standard Acrylic Diffuser

Diffuser Accent Types

DAC	Diffuser Accent Color
CDA	Custom Diffuser Accent

- Standard LED CRI is 80 contact us for alternate CRI availability
 Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
 Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Mounts to standard electrical junction box (by others)
 UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Mountings

 WM Wall Mount

Louvers

SQ Square Cell

Dimming Types

0 D1 2 D3

Options

SIL Silhouette Symbol LOGO Custom Logo BLBottom Lens