

Roxbury Series Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
RX1024L • W 10 • HT 31 • OAH 72 (OverAll Height)	GBK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ
RX1226L • W 12 • HT 34 • OAH 96 (OverAll Height)	DVD	14,500lm LED (86W)	5,100lm LED (36W)	2	PC	WA	ST CH SM SP	SQ
	DNY	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ
	DNZ	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	DOA	23,100lm LED (146W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ
	ETG	23,100lm LED (146W)	10,400lm LED (76W)	2	PC	WA	ST CH SM SP	SQ
	DOB	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	FIY	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ
RX1231L • W 12 • HT 39 • OAH 96 (OverAll Height)	DXL	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SM SP	SQ
	DOS	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ

	DMF	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	DKO	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	FIZ	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ
RX1236L • W 12 • HT 44 • OAH 96 (OverAll Height)	GKG	10,800lm LED (60W)		1	PC	WA	ST CH SM SP	SQ
	GDZ	15,400lm LED (86W)	5,100lm LED (36W)	2	PC	WA	ST CH SM SP	SQ
	GEF	17,800lm LED (100W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	GES	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	GEV	39,000lm LED (267W)	12,500lm LED (93W)	2	PC	WA	ST CH SM SP	SQ
	GIX	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SM SP	SQ

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 15'
 DOOR HEIGHT: 7'
 SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed

Abbreviation Key

Lamps

60W A19

Medium Base, 60W Max, Incandesent or LED

100W PAR38

Medium Base, 100W Max, Incandesent or LED

Finish Types

PC

Powder Coat

Diffuser Types

WA

Standard Acrylic Diffuser

Mountings

ST

Stem

CH

Chain

SM

Surface Mount Chain

SP

Steep Pitch Canopy for Stem

Louvers

SQ

Square Cell

Dimming Types

0

D1

1

D2

2

D3

- [Contact Us](#) for more lamping options.