San Antonio Series Ceiling Mount






Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mountin
SA1806C	EDX	2,600lm LED (22W)	1	PC	WA	CC
• W 18" • HT 9"					PA	FM
	BCR	2-60W A19 (120W)	1	PC	WA PA	CC FM
SA2408C	EDY	2,600lm LED (22W)	1	PC	WA	CC
• W 24" • HT 11"					PA	FM
	GHC	5,400lm LED (39W)	1	PC	WA PA	CC FM
	EOO	7,700lm LED (53W)	1	PC	WA PA	CC FM
	BCT	3-60W A19 (180W)	1	PC	WA PA	CC FM
SA3010C	EOP	7,700lm LED (58W)	1	PC	WA PA	CC FM
• W 30" • HT 12"					FA	ΓM
	EOQ	13,600lm LED (96W)	1	PC	WA PA	CC FM
	BHR	3-100W A21 (300W)	1	PC	WA PA	CC FM
5A3612C	EOR	16,500lm LED (101W)	1	РС	WA	CC
• W 36" • HT 13"					PA	FM
	BHT	3-100W A21 (300W)	1	PC	WA PA	CC FM

SA4214C	EOT	23,400lm LED (159W)	1	PC	WA PA	CC FM
• W 42" • HT 15"						
	FJU	6-60W A19 (360W)	1	PC	WA PA	CC FM

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- · Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driverWired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation	Кеу
Lamps	
60W A19	Medium Base, 60W Max, Incandesent or LED
100W A21	Medium Base, 100W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Diffuser Type	S
WA	Standard Acrylic Diffuser
РА	Premium Acrylic Diffuser
Mountings	
СС	Ceiling Canopy
FM	Flush Mount
Dimming Typ	es

0

D1