

Sacramento Series Ceiling Mount



SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Hanging - Diffuser - Options

Model	Lamping Options										
Model Number	Lamping Code	Body Lamping	Voltage	Circuit	Finish	Louver	Hanging	Diffuser	Options	Dimensions	
SC1806C	EDX	2,900lm LED (30W)	120/277	1	PC	SQ	CC	AD	DM	W	18"
	BCS	2-F26TBX (58W)	120/277	1	PB			FA	FD	HT	9"
	BCR	2-60A19 (120W)	120	1						OAH	N/A
SC2408C	EDY	2,900lm LED (30W)	120/277	1	PC	SQ	CC	AD	DM	W	24"
	EEH	6,300lm LED (24W)	120/277	1	PB			FA	FD	HT	11"
	BCU	2-F32TBX (77W)	120/277	1						OAH	N/A
	EDZ	2-F42TBX (99W)	120/277	1							
	BCT	3-60A19 (180W)	120	1							
SC3010C	BHS	2-F42TBX (99W)	120/277	1	PC	SQ	CC	AD	DM	W	30"
	CUH	4-F32TBX (154W)	120/277	1	PB			FA	FD	HT	12"
	BHR	3-100A19 (300W)	120	1						OAH	N/A
SC3612C	BHU	4-F42TBX (197W)	120/277	1	PC	SQ	CC	AD	DM	W	36"
	BHT	3-150A21 (450W)	120	1	PB			FA	FD	HT	13"
										OAH	N/A
SC4214C	BHW	6-F42TBX (296W)	120/277	1	PC	SQ	CC	AD	DM	W	42"
	DAS	8-F42TBX (394W)	120/277	1	PB			FA	FD	HT	15"
	BHV	6-100A19 (600W)	120	1						OAH	N/A

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic ballast or LED driver

Abbreviation Key

Dimensions

W	Width
HT	Height
OAH	Overall Height

Lamp Descriptions

60A19	60W A19, medium base
100A19	100W A19, medium base
150A21	150W A21, medium base
F26TBX	26W triple biax, 4-PIN GX24q-3 base
F32TBX	32W triple biax, 4-PIN GX24q-3 base

- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Mounts to standard 4" octagonal electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

F42TBX 42W triple biax, 4-PIN GX24q-4 base
LED 3000 Kelvin Warm White LED

Finishes

PC Powder Coat
PB Polished Brass

Hanging Style

CC Ceiling Canopy

Diffusers

AD Acrylic (White Acrylic Standard)
FA Faux Alabaster

Options

DM Dimming
DIM-010 0-10V four wire control dimming
FD Frosted Diffuser

Louver

SQ SQUARE CELL (Must be used on all LED lamping)