

San Francisco Series Ceiling Mount



Model Number	Lamping Code	Body Lamping	Up Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting
SF1806C • W 18" • HT 9"	EDV	2,600lm LED (22W)			1	PC	WA PA	CC FM
	BEZ	2-60W A19 (120W)			1	PC	WA PA	CC FM
SF2409C • W 24" • HT 12"	EDW	3,800lm LED (31W)			1	PC	WA PA	CC FM
	BFB	3-60W A19 (180W)			1	PC	WA PA	CC FM
SF3010C • W 30" • HT 13"	ETA	9,600lm LED (70W)	3,200lm LED	6,400lm LED	1	PC	WA PA	CC FM
	BHI	3-100W A21 (300W)			1	PC	WA PA	CC FM
SF3612C • W 36" • HT 15"	ETB	16,400lm LED (119W)	10,900lm LED	5,400lm LED	1	PC	WA PA	CC FM
	BHL	3-100W A21 (300W)			1	PC	WA PA	CC FM
SF4214C • W 42" • HT 17"	ETC	19,000lm LED (132W)	14,200lm LED	4,700lm LED	1	PC	WA PA	CC FM
	FJQ	6-60W A19 (360W)			1	PC	WA PA	CC FM

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19	Medium Base, 60W Max, Incandescent or LED
100W A21	Medium Base, 100W Max, Incandescent or LED

Finish Types

PC	Powder Coat
----	-------------

Diffuser Types

WA	Standard Acrylic Diffuser
PA	Premium Acrylic Diffuser

Mountings

CC	Ceiling Canopy
FM	Flush Mount

Dimming Types

0	D1
---	----