


San Francisco Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SF1814B	EMS	3,200lm LED (20W)	1	PC	WA PA	WM
	• W 18" • HT 14"					
	BFH	1-100W A21 (100W)	1	PC	WA PA	WM
SF2417B	EMT	3,200lm LED (20W)	1	PC	WA PA	WM
	• W 24" • HT 17"					
	BFJ	1-100W A21 (100W)	1	PC	WA PA	WM

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic bowl diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature

Abbreviation Key

Lamps

100W A21Medium Base, 100W Max, Incandesent or LED

Finish Types

PCPowder Coat

Diffuser Types

WAStandard Acrylic Diffuser

PAPremium Acrylic Diffuser

Mountings

WMWall Mount

Dimming Types

availability

- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

0

D1