

Spokane Series 3-Arm Cluster Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SP5015U • W 72" • HT 15" • OAH 36" (OverAll Height)	EVX	23,200lm LED (173W)	1	PC	WA PA	ST SP MS
	EVY	30,500lm LED (231W)	1	PC	WA PA	ST SP MS
	EWI	12-100W A21 (1200W)	1	PC	WA PA	ST SP MS
SP6217U • W 90" • HT 17" • OAH 48" (OverAll Height)	EVZ	27,700lm LED (173W)	1	PC	WA PA	ST SP MS
	EWA	37,900lm LED (288W)	1	PC	WA PA	ST SP MS
	EWJ	18-100W A21 (1800W)	1	PC	WA PA	ST SP MS

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES	Abbreviation Key
- Fabricated and welded metal housing - Powder coated metallic finish - UV stable, white acrylic bowl diffuser (Standard) - Optional specialty diffuser materials available - Energy efficient LED lamping - High power factor electronic LED driver - Wired for dual circuit operation, Body Lamping and Down Lamping - Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability - Standard LED CRI is 80 - contact us for alternate CRI availability - Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility. - Standard LED dimming is 0-10v - Optional line voltage (Triac or ELV) LED dimming is available - consult for	
	Lamps
	100W A21 Medium Base, 100W Max, Incandesent or LED
	Finish Types
	PC Powder Coat
	Diffuser Types
	WA Standard Acrylic Diffuser

- compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

PA Premium Acrylic Diffuser

Mountings

ST	Stem
SP	Steep Pitch Canopy for Stem
MS	Multi-Stem

Dimming Types

0	D1
---	----