

Spokane Series Wall Sconce



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
SP1808S • W 18" • HT 8"	EOI	1,400lm LED (11W)	1	PC	WA PA	WM
	DWR	2-100W A21 (200W)	1	PC	WA PA	WM
SP2410S • W 24" • HT 10"	EDU	2,300lm LED (18W)	1	PC	WA PA	WM
	BFF	2-100W A21 (200W)	1	PC	WA PA	WM

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES • Fabricated and welded metal housing • Powder coated metallic finish • UV stable, white acrylic bowl diffuser (Standard) • Optional specialty diffuser materials available • Energy efficient LED lamping • High power factor electronic LED driver • Wired for single circuit operation, Body Lamping • Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability • Standard LED CRI is 80 - contact us for alternate CRI availability • Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility. • Standard LED dimming is 0-10v • Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility • Mounts to standard electrical junction box (by others) • UL / cUL or ETL / cETL listed • Contact Us for more lamping options.	Abbreviation Key	
	Lamps	
	100W A21	Medium Base, 100W Max, Incandesent or LED
	Finish Types	
	PC	Powder Coat
	Diffuser Types	
	WA	Standard Acrylic Diffuser
	PA	Premium Acrylic Diffuser
	Mountings	
	WM	Wall Mount
	Dimming Types	

