Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

Savannah Series Wall Bracket






Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
SV0816B • W 8" • HT 16" • EXT 11"	AHZ	1-100W A21 (100W)	1	PC	WA	WM	SQ	SIL LOGO BL
SV1020B • W 10" • HT 20" • EXT 13"	DEM	3,900lm LED (24W)	1	PC	WA	WM	SQ	SIL LOGO BL
	AIB	1-100W A21 (100W)	1	PC	WA	WM	SQ	SIL LOGO BL
SV1224B • W 12" • HT 24" • EXT 15"	FFX	5,400lm LED (33W)	1	PC	WA	WM	SQ	SIL LOGO BL
	GBW	2-100W A21 (200W)	1	PC	WA	WM	SQ	SIL LOGO BL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)

Abbreviation Key

Lamps

100W A21	Medium Base, 100W Max, Incandesent or LED

Finish Types

PC	Powder Coat

Diffuser Types

WA	Standard Acrylic Diffuser

Mountings

WM	Wall Mount

- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Louvers	
SQ	Square Cell

Dimming Types	
0	D1
1	D3

Options	
SIL	Silhouette Symbol
LOGO	Custom Logo
BL	Bottom Lens