Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

Waycross Series Wall Sconce

Model Number	Lamping Code	Body Lamping	Circuit	Finish	Finish Accent	Diffuser	Mounting	Louver	Options
WC0816S • W 11 • HT 18 • EXT 6	DYW	1,000lm LED (7W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
	DYK	1,800lm LED (14W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
	AHS	1-60W A19 (60W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
WC1020S • W 14 • HT 22 • EXT 7	DYL	1,800lm LED (14W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
	DYM	3,100lm LED (22W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
	AHU	2-100W A21 (200W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
WC1224S • W 16 • HT 27 • EXT 8	DYO	6,300lm LED (40W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
	DYN	7,100lm LED (44W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL
	AHX	3-100W A21 (300W)	1	PC	WT CT	WA	WM	BD	SIL LOGO BL

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

Abbreviation Key

Lamps

60W A19	Medium Base, 60W Max, Incandesent or LED
100W A21	Medium Base, 100W Max, Incandesent or LED

Finish Types

PC	Powder Coat



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- Stained Solid Red Oak Wood Trim
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Finish Accent Types	
WT	Wood Trim
CT	Custom Trim

Diffuser Types	
WA	Standard Acrylic Diffuser

Mountings	
WM	Wall Mount

Louvers	
BD	Bottom Perf Door

Dimming Types	
0	D1
1	D2
2	D3

Options	
SIL	Silhouette Symbol
LOGO	Custom Logo
BL	Bottom Lens
BD	Bottom Door