

Woodland Series Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Finish Accent	Diffuser	Mounting	Louver
WD1024L	GBK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WT CT	WA	ST CH SM SP	SQ
• W 14 • HT 26 • OAH 72 (OverAll Height)									
WD1226L	DVD	14,500lm LED (86W)	5,100lm LED (36W)	2	PC	WT CT	WA	ST CH SM SP	SQ
• W 16 • HT 29 • OAH 96 (OverAll Height)									
	DNY	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	DNZ	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	DOA	23,100lm LED (146W)	7,100lm LED (51W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	ETG	23,100lm LED (146W)	10,400lm LED (76W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	DOB	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	FIY	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WT CT	WA	ST CH SM SP	SQ
WD1231L	DXL	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WT CT	WA	ST CH SM SP	SQ
• W 16 • HT 34 • OAH 96 (OverAll Height)									
	DOS	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ

	DMF	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	DKO	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	FIZ	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WT CT	WA	ST CH SM SP	SQ
WD1236L • W 12" • HT 36" • OAH 96" (OverAll Height)	GKG	10,800lm LED (60W)		1	PC	WT CT	WA	ST CH SM SP	SQ
	GDZ	15,400lm LED (86W)	5,100lm LED (36W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	GEF	17,800lm LED (100W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	GES	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	GEV	39,000lm LED (267W)	12,500lm LED (93W)	2	PC	WT CT	WA	ST CH SM SP	SQ
	GIX	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WT CT	WA	ST CH SM SP	SQ

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- Stained Solid Red Oak Wood Trim
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)

Abbreviation Key

Lamps

- 60W A19Medium Base, 60W Max, Incandesent or LED
- 100W PAR38Medium Base, 100W Max, Incandesent or LED

Finish Types

- PCPowder Coat

Finish Accent Types

- WTWood Trim
- CTCustom Trim

Diffuser Types

- WASandard Acrylic Diffuser

Mountings

- STStem
- CHChain
- SMSurface Mount Chain
- SPSteep Pitch Canopy for Stem

Louvers

- SQSquare Cell

Dimming Types

- 0D1

- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

1
2

D2
D3