


Woodstock Series Wall Sconce WS1030S






Model Number	Lamping Code	Body Lamping	Circuit
WS1030S	DQA	2,600lm LED (21W)	1
• W 10" • HT 12" • EXT 4"	BTE	1-40W T10 (40W)	

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



Abbreviation Key

Lamps

40W T10 40W T10, medium base

Dimming Types

D1

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- · Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility

- Mounts to standard electrical junction box (by others)
 UL / cUL or ETL / cETL listed
 Contact Us for more lamping options.