

Woodstock Series Wall Sconce WS2112S



Model Number	Lamping Code	Body Lamping	Circuit
WS2112S	DQB	2,100lm LED (16W)	1
	GKZ	3,400lm LED (25W)	1
	BUC	2-60W A19 (120W)	1

- W 9"
- HT 20"
- EXT 4"

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

Abbreviation Key

Lamps

60W A19Medium Base, 60W Max, Incandesent or LED

Dimming Types

0D1

2D2

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability

- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.