

Wichita Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Finish Accent	Diffuser	Mounting	Louver	Options
WT0816B	AHZ	1-100W A21 (100W)	1	PC	WT CT	WA	WM	SQ	SIL LOGO BL
	• W 11 • HT 18 • EXT 14								
WT1020B	DEM	3,900lm LED (24W)	1	PC	WT CT	WA	WM	SQ	SIL LOGO BL
	• W 14 • HT 22 • EXT 17								
	AIB	1-100W A21 (100W)	1	PC	WT CT	WA	WM	SQ	SIL LOGO BL
WT1224B	FFX	5,400lm LED (33W)	1	PC	WT CT	WA	WM	SQ	SIL LOGO BL
	• W 16 • HT 27 • EXT 18								
	GBW	2-100W A21 (200W)	1	PC	WT CT	WA	WM	SQ	SIL LOGO BL

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- Stained Solid Red Oak Wood Trim

Abbreviation Key

Lamps

100W A21Medium Base, 100W Max, Incandesent or LED

Finish Types

PCPowder Coat

Finish Accent Types

WTWood Trim

CTCustom Trim

Diffuser Types

WASandard Acrylic Diffuser

- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Mountings	
WM	Wall Mount
Louvers	
SQ	Square Cell
Dimming Types	
0	D1
2	D3
Options	
SIL	Silhouette Symbol
LOGO	Custom Logo
BL	Bottom Lens