



Bismarck Series Short Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver
BM1008P • W 12 • HT 9 • OAH 48 (OverAll Height)	GGV	4,800lm LED (14W)	1	PC	WA AG	ST SP	SQ
	AXL	2-100W A21 (200W)	1	PC	WA AG	ST SP	SQ
BM1309P • W 15 • HT 10 • OAH 48 (OverAll Height)	GGW	4,800lm LED (27W)	1	PC	WA AG	ST SP	SQ
	AXN	3-100W A21 (300W)	1	PC	WA AG	ST SP	SQ
BM1410P • W 14" • HT 10" • OAH 48" (OverAll Height)	GGX	4,800lm LED (27W)	1	PC	WA AG	ST SP	SQ
	CWX	3-150W A21 (450W)	1	PC	WA AG	ST SP	SQ
BM2408P • W 26 • HT 8 • OAH 48 (OverAll Height)	GKX	9,700lm LED (58W)	1	PC	WA AG	ST SP	SQ
	GKW	15,800lm LED (116W)	1	PC	WA AG	ST SP	SQ

SAMPLE CATALOG NUMBER	
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options	
Scale	Abbreviation Key
	Lamps
	100W A21 Medium Base, 100W Max, Incandesent or LED



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

150W A21 Medium Base, 150W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

AG Premium Glass Diffuser

Mountings

ST Stem

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

0 D1

1 D2