Brookville Series Wall Bracket





| Model Number | Lamping Code | Body Lamping | Circu | t Finish | Diffuser | Diffuser Accent | Mounting | Louver | Options |
|----------------------------|-----------------|-------------------|-------|----------|----------|--------------------|----------|--------|-------------------|
| • W 10" • HT 20" • EXT 13" | FMB | 1-100W A21 (100W) | 1 | PC | WA AG | DAC CDA | WM | SQ | CUT LOGO BL |
| BR1326B • W 13" • HT 26" | FMF | 2-100W A21 (200W) | 1 | PC | WA AG | DAC CDA | WM | SQ | CUT LOGO BL |

SAMPLE CATALOG NUMBER

• EXT 15"

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

CEILING HEIGHT: 9' DOOR HEIGHT: 7' SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser
AG Premium Glass Diffuser

Diffuser Accent Types

DAC Diffuser Accent Color
CDA Custom Diffuser Accent

Mountings

WM Wall Mount

- manufacturer for compatibility.

 Standard LED dimming is 0-10v

 Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility

 Mounts to standard electrical junction box (by others)

 UL / cUL or ETL / cETL listed

 Contact Us for more lamping options.

Louvers

Square Cell SQ

Options

CUT Cut-Out Symbol LOGO Custom Logo BL Bottom Lens