


Cambridge Series Pendant




Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louwer
CA1222L	AAD	3-100W-A21 (300W)	1-300W-R40 (300W)	2	PC	AD AG	ST TC	CR SQ
<ul style="list-style-type: none"> • W 12" • HT 25" • OAH 72" (OverAll Height) 								
CA1426L	DVG	14,500lm LED (88W)	5,000lm LED (33W)	2	PC	AD AG	ST TC	CR SQ
<ul style="list-style-type: none"> • W 14" • HT 29" • OAH 96" (OverAll Height) 								
	DFB	14,500lm LED (88W)	7,000lm LED (47W)	2	PC	AD AG	ST TC	CR SQ
	DTG	14,500lm LED (88W)	12,000lm LED (100W)	2	PC	AD AG	ST TC	CR SQ
	DFJ	23,100lm LED (146W)	12,000lm LED (100W)	2	PC	AD AG	ST TC	CR SQ
	DHI	6-100W-A21 (600W)	1-300W-R40 (300W)	2	PC	AD AG	ST TC	CR SQ
CA1631L	DFA	14,500lm LED (88W)	12,000lm LED (100W)	2	PC	AD AG	ST TC	CR SQ
<ul style="list-style-type: none"> • W 16" • HT 35" • OAH 96" (OverAll Height) 								
	DLX	23,100lm LED (146W)	12,000lm LED (100W)	2	PC	AD AG	ST TC	CR SQ
	DCR	29,500lm LED (194W)	12,000lm LED (100W)	2	PC	AD AG	ST TC	CR SQ
	DHJ	6-100W-A21 (600W)	1-300W-R40 (300W)	2	PC	AD AG	ST TC	CR SQ

CA1836L	DDL	23,500lm LED (131W)	12,000lm LED (100W)	2	PC	AD AG	ST TC	CR SQ
<ul style="list-style-type: none"> • W 18" • HT 40" • OAH 120" (OverAll Height) 								
	DHK	9-100W-A21 (900W)	1-300W-R40 (300W)	2	PC	AD AG	ST TC	CR SQ
CA2242L	DNF	32,300lm LED (197W)	12,000lm LED (100W)	2	PC	AD AG	ST TC	CR SQ
<ul style="list-style-type: none"> • W 22" • HT 46" • OAH 120" (OverAll Height) 								
	FCC	9-100W-A21 (900W)	1-300W-R40 (300W)	3	PC	AD AG	ST TC	CR SQ

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED or fluorescent lamping
- Wired for dual circuit operation (Body Lamping/Down Lamping)
- High power factor electronic ballast or LED driver
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatability.
- Optional dimming ballast 120V or 277V (LED or fluorescent lamping)
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Dimensions

W	Width
HT	Height
OAH	OverAll Height

Lamps

100W-A21	Medium Base, 100W Max, Incandesent or LED
300W-R40	300W R40, medium base

Finish Types

PC	Powder Coat
----	-------------

Diffuser Types

AD	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings

ST	Stem
TC	Triple Chain Spreader

Louvers

CR	Concentric Ring
SQ	Square Cell

Options

D1	LED 0-10V low voltage control dimming
D2	LED Triac/ELV-phase dimming