

Chandler Series Wall Bracket



| Model Number | Lamping Code | Body Lamping | Down Lamping | Circuit | Finish | Mounting |
|---------------------------|-----------------|-------------------------|-------------------|---------|--------|----------|
| CH0816B • W 8" • HT 16" | FDF | | 5,100lm LED (33W) | 1 | PC | WM |
| • EXT 11" | DZL | | 7,100lm LED (47W) | 1 | PC | WM |
| | FFJ | | 1-100W A21 (100W) | 1 | PC | WM |
| CH0820B | GHA | 2-100W R40/Par38 (200W) | | 1 | PC | WM |

- W 8"
- HT 20"
- EXT 11"

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- · Powder coated metallic finish
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
 Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
 Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC **Powder Coat**

Mountings

WM Wall Mount

Dimming Types

D1 0

D2

2