


Chandler Series Yoke Swivel



Model Number	Lamping Code	Down Lamping	Circuit	Finish	Mounting
CH0819Y • W 8" • HT 19"	GBO	5,000lm LED (32W)	1	PC	YS
	GBQ	7,000lm LED (50W)	1	PC	YS
	GBT	10,000lm LED (72W)	1	PC	YS
	GBV	12,500lm LED (93W)	1	PC	YS

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale	Abbreviation Key
	Finish Types
	PC Powder Coat
	Mountings
	YS Yoke Swivel
PRODUCT FEATURES	Dimming Types
	0 D1
	1 D2
	2 D3

- Fabricated and welded metal housing
- Powder coated metallic finish
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature

availability

- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.