
Cleveland Series Short Pendant






Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louve
• W 12 • HT 7 • OAH 48 (OverAll Height)	АНК	2-100W A21 (200W)	1	PC	WA	ST CH SM SP	SQ
• W 14 • HT 8 • OAH 48 (OverAll Height)	GGQ	5,400lm LED (33W)	1	PC	WA	ST CH SM SP	SQ
	АНМ	3-100W A21 (300W)	1	PC	WA	ST CH SM SP	SQ

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

Mountings

ST Stem CH Chain

SM Surface Mount Chain

SP Steep Pitch Canopy for Stem

- Fabricated and welded metal housingPowder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials availableEnergy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- $\bullet\,$ Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Louvers

SQ Square Cell

Dimming Types

D1 0 1 D2