
Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

Charleston Series 6-Arm Satellite Pendant




Model Number	Lamping Code	Body Lamping	Satellite Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
CR4836A • W 48 • HT 40 • OAH 96 (OverAll Height) • X 1 @ 14"x40" • Y 6 @ 10"x21"	EIB	5-60W A19 (300W)	12-60W A19 (720W)	1-26W PAR38 LED (26W)	3	PC	WA AG	ST CH SP	SQ	CUT LOGO
CR6045A • W 60 • HT 49 • OAH 120 (OverAll Height) • X 1 @ 16"x49" • Y 6 @ 12"x26"	EIC	9-60W A19 (540W)	12-60W A19 (720W)	1-26W PAR38 LED (26W)	3	PC	WA AG	ST CH SP	SQ	CUT LOGO
CR7254A • W 72 • HT 59 • OAH 120 (OverAll Height) • X 1 @ 18"x59" • Y 6 @ 14"x28"	EID	12-60W A19 (720W)	12-60W A19 (720W)	1-26W PAR38 LED (26W)	3	PC	WA AG	ST CH SP	SQ	CUT LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale



Abbreviation Key

Lamps

60W A19	Medium Base, 60W Max, Incandesent or LED
26W PAR38 LED	Medium Base, 26W Max, LED

Finish Types

PC	Powder Coat

Diffuser Types

WA	Standard Acrylic Diffuser

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for three circuit operation, Body Lamping, Down Lamping and Satellite Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

AG	Premium Glass Diffuser

Mountings	
ST	Stem
CH	Chain
SP	Steep Pitch Canopy for Stem

Louvers	
SQ	Square Cell

Options	
CUT	Cut-Out Symbol
LOGO	Custom Logo