

Corvallis Series Wall Bracket



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
CV0816B	ATE	1-100W A21 (100W)	1	PC	WA	WM	SQ	BL

- W 8
- HT 17
- EXT 12

CV1020B	ATG	1-100W A21 (100W)	1	PC	WA	WM	SQ	BL
---------	-----	-------------------	---	----	----	----	----	----

- W 10
- HT 21
- EXT 14

CV1224B	GBY	2-100W A21 (200W)	1	PC	WA	WM	SQ	BL
---------	-----	-------------------	---	----	----	----	----	----

- W 12
- HT 25
- EXT 17

SAMPLE CATALOG NUMBER
Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 9'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)

Abbreviation Key

Lamps

100W A21Medium Base, 100W Max, Incandesent or LED

Finish Types

PCPowder Coat

Diffuser Types

WASandard Acrylic Diffuser

Mountings

WMWall Mount

- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for single circuit operation, Body Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Mounts to standard electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Louvers	
SQ	Square Cell
Options	
BL	Bottom Lens