



Hampton Series 2-Tier Large Pendant





Model Number	Lamping Code	Gallery Lamping	Down Lamping	Circuit	Finish	Finish Accent		Mounting	Louver	Options
HA2412W	FYS	11,900lm LED(77W)		1	PC	WT CT	WA AG	TC	SQ	SIL LOGO
• W 26 • HT 12 • OAH 48 (OverAll Height)	GLI	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO
HA3014W	FYT	17,300lm LED (116W)		1	PC	WT CT	WA AG	TC	SQ	SIL LOGO
• W 32 • HT 14 • OAH 72 (OverAll Height)	GLJ	6-60W A19 (360W)	1-100W R40/Par38 (100W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO
HA3616W	DVJ	35,200lm LED (216W)	7,100lm LED (51W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO
• W 38 • HT 16 • OAH 96 (OverAll Height)	FWH	6-100W A21 (600W)	1-100W R40/Par38 (100W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO
• W 44 • HT 18 • OAH 96 (OverAll Height)	DZT	35,200lm LED (216W)	12,500lm LED (93W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO
	FWI	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO
HA5422W	DVL	42,200lm LED (260W)	12,500lm LED (93W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO
• W 54" • HT 22" • OAH 120" (OverAll Height)	FWJ	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	2	PC	WT CT	WA AG	TC	SQ	SIL LOGO



PRODUCT FEATURES

- Fabricated and welded metal housing
- · Powder coated metallic finish
- Stained Solid Red Oak Wood Trim
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Gallery Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED
100W PAR38 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Finish Accent Types

WT Wood Trim
CT Custom Trim

Diffuser Types

WA Standard Acrylic Diffuser
AG Premium Glass Diffuser

Mountings

TC Triple Chain Spreader

Louvers

SQ Square Cell

Dimming Types

0 D1 1 D2 2 D3

Options

SIL Silhouette Symbol
LOGO Custom Logo