

Hampton Series 3-Tier Large Pendant




(OverAll Height)



| Model Number | Lamping Code | Body Lamping | Gallery Lamping | Down Lamping | Circuit | Finish | Finish Accent | Diffuser | Mounting | Louver | Options |
|--|-----------------|---------------------|---------------------|----------------------------|---------|--------|------------------|----------|----------------|--------|-------------|
| • W 32 • HT 38 • OAH 72 (OverAll Height) | GLG | 4-60W A19 (240W) | 6-60W A19 (360W) | 1-100W R40/Par38 (100W) | 2 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| • W 38 • HT 40 • OAH 96 (OverAll Height) | DVO | 15,300lm LED (87W) | 32,600lm LED (216W) | 7,100lm LED (51W) | 2 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| | FWD | 6-100W A21 (600W) | 6-100W A21 (600W) | 1-100W R40/Par38 (100W) | 3 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| • W 44 • HT 48 • OAH 120 (OverAll Height) | EAU | 15,300lm LED (87W) | 32,600lm LED (216W) | 12,500lm LED (93W) | 2 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| | FWC | 6-100W A21 (600W) | 12-100W A21 (1200W) | 1-100W R40/Par38 (100W) | 3 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| • W 50 • HT 56 • OAH 120 (OverAll Height) | ESP | 25,700lm LED (159W) | 32,600lm LED (216W) | 12,500lm LED (93W) | 2 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| | FWM | 6-100W A21 (600W) | 12-100W A21 (1200W) | 1-100W R40/Par38 (100W) | 3 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| • W 54" • HT 60" • OAH 120" (OverAll Height) | FZD | 27,800lm LED (132W) | 37,600lm LED (260W) | 12,500lm LED (93W) | 2 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| | FWE | 6-100W A21 (600W) | 12-100W A21 (1200W) | 1-100W R40/Par38 (100W) | 3 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |
| • W 60" • HT 72" • OAH 120" | GLR | 27,800lm LED (146W) | 37,600lm LED (260W) | 12,500lm LED (93W) | 2 | PC | WT CT | WA AG | ST CH SP | SQ | SIL LOGO |

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- · Fabricated and welded metal housing
- · Powder coated metallic finish
- Stained Solid Red Oak Wood Trim
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for three circuit operation, Body Lamping, Gallery Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED

100W Medium Base, 100W Max, Incandesent or LED

R40/Par38

Finish Types

PC Powder Coat

Finish Accent Types

WT Wood Trim
CT Custom Trim

Diffuser Types

WA Standard Acrylic Diffuser
AG Premium Glass Diffuser

Mountings

ST Stem
CH Chain

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

0 D1 1 D3

Options

SIL Silhouette Symbol LOGO Custom Logo