


Hampton Series Short Pendant




Model Number	Lamping Code	Body Lamping	Circuit	Finish	Finish Accent	Diffuser	Mounting	Louver	Options
HA1207P • W 14 • HT 7 • OAH 48 (OverAll Height)	ABL	2-100W A21 (200W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
HA1408P • W 16 • HT 8 • OAH 48 (OverAll Height)	GGP	5,400lm LED (33W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
	ABN	3-100W A21 (300W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
HA1609P • W 18 • HT 9 • OAH 48 (OverAll Height)	GGS	5,400lm LED (33W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
	ABP	3-100W A21 (300W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
HA1610P • W 16" • HT 10" • OAH 48" (OverAll Height)	GKP	5,400lm LED (33W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
	GKO	3-100W A21 (300W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
HA1811P • W 20 • HT 11 • OAH 48 (OverAll Height)	GGT	5,400lm LED (33W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
	ABR	3-100W A21 (300W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
HA2208P • W 24 • HT 8 • OAH 48 (OverAll Height)	ENE	9,700lm LED (58W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO

ENF	15,800lm LED (116W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO
GIT	6-60W A19 (360W)	1	PC	WT CT	WA AG	ST CH SM SP	SQ	SIL LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- Stained Solid Red Oak Wood Trim
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key	
Lamps	
100W A21	Medium Base, 100W Max, Incandesent or LED
60W A19	Medium Base, 60W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Finish Accent Types	
WT	Wood Trim
CT	Custom Trim
Diffuser Types	
WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser
Mountings	
ST	Stem
CH	Chain
SM	Surface Mount Chain
SP	Steep Pitch Canopy for Stem
Louvers	
SQ	Square Cell
Dimming Types	
0	D1
1	D2
2	D3
Options	
SIL	Silhouette Symbol
LOGO	Custom Logo