

Hebron Series 2-Tier Large Pendant





| Model Number | Lamping Code | Gallery Lamping | Down Lamping | Circuit | Finish | Diffuser | Mounting | Louver | Options |
|---|-----------------|---------------------|-------------------------|---------|--------|----------|----------|--------|-------------|
| HB2412W | FYS | 11,900lm LED (77W) | | 1 | PC | WA AG | тс | SQ | SIL LOGO |
| • W 24" • HT 12" • OAH 48" (OverAll Height) | GLI | 6-60W A19 (360W) | 1-100W PAR38 (100W) | 2 | PC | WA AG | TC | SQ | SIL LOGO |
| HB3014W | FYT | 17,300lm LED (116W) | | 1 | PC | WA AG | ТС | SQ | SIL LOGO |
| • W 30" • HT 14" • OAH 72" (OverAll Height) | GLJ | 6-60W A19 (360W) | 1-100W R40/Par38 (100W) | 2 | PC | WA AG | TC | SQ | SIL LOGO |
| HB3616W | DVJ | 35,200lm LED (216W) | 7,100lm LED (51W) | 2 | PC | WA AG | TC | SQ | SIL LOGO |
| • W 36" • HT 16" • OAH 96" (OverAll Height) | FWH | 6-100W A21 (600W) | 1-100W R40/Par38 (100W) | 2 | PC | WA AG | TC | SQ | SIL LOGO |
| HB4218W | DZT | 35,200lm LED (216W) | 12,500lm LED (93W) | 2 | PC | WA AG | тс | SQ | SIL LOGO |
| • W 42" • HT 18" • OAH 96" (OverAll Height) | FWI | 12-100W A21 (1200W) | 1-100W R40/Par38 (100W) | 2 | PC | WA AG | TC | SQ | SIL LOGO |
| HB5422W | DVL | 42,200lm LED (260W) | 12,500lm LED (93W) | 2 | PC | WA AG | ТС | SQ | SIL LOGO |
| • W 54" • HT 22" • OAH 120" (OverAll Height) | FWJ | 12-100W A21 (1200W) | 1-100W R40/Par38 (100W) | 2 | PC | WA AG | тс | SQ | SIL LOGO |



PRODUCT FEATURES

- · Fabricated and welded metal housing
- · Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- · Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Gallery Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- · Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

| Lamps | |
|------------|---|
| 60W A19 | Medium Base, 60W Max, Incandesent or LED |
| 100W PAR38 | Medium Base, 100W Max, Incandesent or LED |

| Finish Types | |
|----------------|---------------------------|
| PC | Powder Coat |
| | |
| Diffuser Types | |
| WA | Standard Acrylic Diffuser |
| AG | Premium Glass Diffuser |
| | |
| Mountings | |
| тс | Triple Chain Spreader |
| | |
| Louvers | |
| SQ | Square Cell |
| | |
| Dimming Types | 5 |
| 0 | D2 |
| 1 | D1 |
| 2 | D3 |
| | |
| Options | |
| SIL | Silhouette Symbol |
| LOGO | Custom Logo |
| | |
| | |