Hebron Series Intermediate Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
HB1418Q • W 14" • HT 18" • OAH 48" (OverAll Height)	DVC	6,800lm LED(40W)	5,100lm LED (33W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	DKZ	6,800lm LED (40W)	7,100lm LED (47W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	EGC	13,300lm LED (87W)	5,100lm LED(33W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	EGD	13,300lm LED (87W)	7,100lm LED(47W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	FJZ	3-100W A21 (300W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)

Abbreviation Key

Lamps	
100W A21	Medium Base, 100W Max, Incandesent or LED
Finish Types	
PC	Powder Coat
Diffuser Types	
WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings

ST Stem

- UL / cUL or ETL / cETL listed
 Contact Us for more lamping options.

СН	Chain		
SM	Surface Mount Chain		
SP	Steep Pitch Canopy for Stem		
Louvers			
SQ	Square Cell		
Dimming Types			
0	D1		

2	D16
3	D3
Options	
SIL	Silhouette Symbol
LOGO	Custom Logo

1

D2