
Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

Hancock Series Ceiling Mount





Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
HC1207C • W 12" • HT 10"	AMY	2-100W A21 (200W)	1	PC	WA AG	CC	SQ	SIL LOGO
HC1408C • W 14" • HT 11"	ANA	3-100W A21 (300W)	1	PC	WA AG	CC	SQ	SIL LOGO
HC1609C • W 16" • HT 12"	GFC	5,400lm LED (33W)	1	PC	WA AG	CC	SQ	SIL LOGO
	ANC	3-100W A21 (300W)	1	PC	WA AG	CC	SQ	SIL LOGO
HC1811C • W 18 • HT 15	GFD	5,400lm LED (33W)	1	PC	WA AG	CC	SQ	SIL LOGO
	ANE	3-100W A21 (300W)	1	PC	WA AG	CC	SQ	SIL LOGO
HC2208C • W 22 • HT 11	FYA	9,700lm LED (58W)	1	PC	WA AG	CC	SQ	SIL LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

Abbreviation Key


Lamps

100W A21	Medium Base, 100W Max, Incandesent or LED

Finish Types

PC	Powder Coat

Diffuser Types



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- Wired for single circuit operation (Body Lamping)
- High power factor electronic LED driver
- Standard LED color temperature is 3000K with 80 CRI. Contact us for other color temperature or CRI options.
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Optional dimming driver 120V (LED lamping)
- Mounts to standard 4" octagonal electrical junction box (by others)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings	
CC	Ceiling Canopy

Louvers	
SQ	Square Cell

Dimming Types	
0	D1
1	D2

Options	
SIL	Silhouette Symbol
LOGO	Custom Logo