


Hancock Series Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
HC1224L • W 12 • HT 26 • OAH 72 (OverAll Height)	GEL	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
HC1426L • W 14 • HT 28 • OAH 96 (OverAll Height)	DNT	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	DNU	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	DNW	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	FIP	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
HC1631L • W 16 • HT 33 • OAH 96 (OverAll Height)	DOU	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	DMB	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	DGD	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	FLP	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
HC1836L • W 18 • HT 39 • OAH 120 (OverAll Height)	FZV	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO

	FZW	35,300lm LED (238W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	FIS	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
HC2242L • W 22 • HT 45 • OAH 120 (OverAll Height)	GLA	31,000lm LED (185W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO
	FIU	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA AG	ST CH SM SP	SQ	SIL LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale

CEILING HEIGHT: 15'
DOOR HEIGHT: 7'
SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19

Medium Base, 60W Max, Incandesent or LED

100W PAR38

Medium Base, 100W Max, Incandesent or LED

Finish Types

PC

Powder Coat

Diffuser Types

WA

Standard Acrylic Diffuser

AG

Premium Glass Diffuser

Mountings

ST

Stem

CH

Chain

SM

Surface Mount Chain

SP

Steep Pitch Canopy for Stem

Louvers

SQ

Square Cell

Dimming Types

0

D1

1

D2

2

D3

Options

SIL

Silhouette Symbol

LOGO

Custom Logo