
Hammond Series 3-Tier Large Pendant





Model Number	Lamping Code	Body Lamping	Gallery Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Options
• W 30 • HT 40 • OAH 72 (OverAll Height)	GLH	4-60W A19 (240W)	6-60W A19 (360W)	1-100W R40/Par38 (100W)	2	PC	WA AG	ST CH SP	SQ	SIL LOGO
• W 36 • HT 44 • OAH 96 (OverAll Height)	DWH	15,300lm LED (87W)	32,600lm LED (216W)	7,100lm LED (51W)	2	PC	WA AG	ST CH SP	SQ	SIL LOGO
	DJH	6-100W A21 (600W)	6-100W A21 (600W)	1-100W R40/Par38 (100W)	3	PC	WA AG	ST CH SP	SQ	SIL LOGO
• W 42 • HT 50 • OAH 120 (OverAll Height)	DWK	15,300lm LED (87W)	32,600lm LED (216W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SP	SQ	SIL LOGO
	FWL	6-100W A21 (600W)	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	3	PC	WA AG	ST CH SP	SQ	SIL LOGO
• W 54" • HT 60" • OAH 120" (OverAll Height)	DWL	28,100lm LED (152W)	37,600lm LED (260W)	12,500lm LED (93W)	2	PC	WA AG	ST CH SP	SQ	SIL LOGO
	ELK	6-100W A21 (600W)	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	3	PC	WA AG	ST CH SP	SQ	SIL LOGO

SAMPLE CATALOG NUMBER

Model Number - Lamping Code - Finish - Mounting - Diffuser - Options

Scale


Abbreviation Key

Lamps

60W A19

Medium Base, 60W Max, Incandesent or LED Medium Base, 100W Max, Incandesent or LED

100W R40/Par38



PRODUCT FEATURES

- Fabricated and welded metal housing
- · Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- · Optional specialty diffuser materials available
- · Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for three circuit operation, Body Lamping, Gallery Lamping and Down Lamping

 Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature
- availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH Over All Height is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Finish Types

PC **Powder Coat**

Diffuser Types

Standard Acrylic Diffuser WA Premium Glass Diffuser AG

Mountings

ST Stem СН Chain

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

D1

Options

SIL Silhouette Symbol LOGO Custom Logo