



Hartford Series 3-Arm Cluster Pendant





Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver	Option
• W 37 • HT 32 • OAH 96 (OverAll Height) • Y 3 @ 12"x26"	GCB	12-60W A19 (720W)	3-100W A19 (300W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
HF3026U	DQK	43,600lm LED (258W)	21,400lm LED (152W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
• W 42 • HT 34 • OAH 96	DQM	69,300lm LED (436W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT

• W 42 • HT 34 • OAH 96 (OverAll Height) • Y 3 @ 14"x29"	DQM	69,300lm LED (436W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	FKW	18-60W A19 (1080W)	3-100W A21 (300W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
• W 53 • HT 39 • OAH 120 (OverAll Height) • Y 3 @ 16"x34"	DQN	43,600lm LED (258W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	DQO	69,300lm LED (436W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	DQP	88,700lm LED (575W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	FKX	18-60W A19 (1080W)	3-100W A21 (300W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
• W 63 • HT 44 • OAH 120 (OverAll Height) • Y 3 @ 18"x40"	GAB	53,600lm LED (298W)	15,500lm LED (108W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	GAC	53,600lm LED (298W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	FYV	74,800lm LED (436W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	FYW	105,900lm LED (713W)	37,600lm LED (278W)	2	PC	WA AG	ST SP	SQ	CUT LOGO
	FKY	27-60W A19 (1620W)	3-100W A21 (300W)	3	PC	WA AG	ST SP	SQ	CUT LOGO



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19 Medium Base, 60W Max, Incandesent or LED
100W A19 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

WA Standard Acrylic Diffuser

AG Premium Glass Diffuser

Mountings

ST Stem

SP Steep Pitch Canopy for Stem

Louvers

SQ Square Cell

Dimming Types

0 D3
1 D1
2 D2

Options

CUT Cut-Out Symbol
LOGO Custom Logo