
Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

# Ipswich Series Pendant







| Model Number | Lamping Code | Body Lamping | Down Lamping | Circuit | Finish | Diffuser | Mounting | Louver |
|---|---|---|---|---|---|---|---|---|
| **IP1224L**<br>• W 12<br>• HT 26<br>• OAH 72<br>(OverAll Height) | GBL | 4-60W A19 (240W) | 1-100W PAR38 (100W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| **IP1426L**<br>• W 14<br>• HT 29<br>• OAH 96<br>(OverAll Height) | DVG | 14,500lm LED (86W) | 5,100lm LED (36W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | DFB | 14,500lm LED (86W) | 7,100lm LED (51W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | DTG | 14,500lm LED (86W) | 12,500lm LED (93W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | EOB | 23,100lm LED (146W) | 7,100lm LED (51W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | DFJ | 23,100lm LED (146W) | 12,500lm LED (93W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | FIH | 6-60W A19 (360W) | 1-100W PAR38 (100W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| **IP1631L**<br>• W 16<br>• HT 34<br>• OAH 96<br>(OverAll Height) | DFA | 14,500lm LED (86W) | 12,500lm LED (93W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | DLX | 23,100lm LED (146W) | 12,500lm LED (93W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | DCR | 29,500lm LED (192W) | 12,500lm LED (93W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | FII | 6-60W A19 (360W) | 1-100W PAR38 (100W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| **IP1836L**<br>• W 18<br>• HT 40<br>• OAH 120 (OverAll Height) | FYJ | 24,900lm LED (146W) | 12,500lm LED (93W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | FIJ | 9-60W A19 (540W) | 1-100W PAR38 (100W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| **IP2242L**<br>• W 22<br>• HT 46<br>• OAH 120 (OverAll Height) | GGO | 31,000lm LED (185W) | 12,500lm LED (93W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |
| | FIL | 9-60W A19 (540W) | 1-100W PAR38 (100W) | 2 | PC | WA<br>AG | ST<br>CH<br>TC<br>SM<br>SP | SQ |

SAMPLE CATALOG NUMBER

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

Scale




**PRODUCT FEATURES**

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

| | |
|---|---|
| 60W A19 | Medium Base, 60W Max, Incandesent or LED |
| 100W PAR38 | Medium Base, 100W Max, Incandesent or LED |

Finish Types

| | |
|---|---|
| PC | Powder Coat |

Diffuser Types

| | |
|---|---|
| WA | Standard Acrylic Diffuser |
| AG | Premium Glass Diffuser |

Mountings

| | |
|---|---|
| ST | Stem |
| CH | Chain |
| TC | Triple Chain Spreader |
| SM | Surface Mount Chain |
| SP | Steep Pitch Canopy for Stem |

Louvers

| | |
|---|---|
| SQ | Square Cell |

Dimming Types

| | |
|---|---|
| 0 | D1 |
| 1 | D2 |
| 2 | D3 |
| 3 | D16 |