



Jamestown Series 2-Tier Large Pendant



Model Number	Lamping Code	Gallery Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
JT2412W • W 24" • HT 12" • OAH 48" (OverAll Height)	FYS	11,900lm LED (77W)		1	PC	WA AG	TC	SQ
	GLI	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA AG	TC	SQ
JT3014W • W 30" • HT 14" • OAH 72" (OverAll Height)	FYT	17,300lm LED (116W)		1	PC	WA AG	TC	SQ
	GLJ	6-60W A19 (360W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ
JT3616W • W 36" • HT 16" • OAH 96" (OverAll Height)	DVJ	35,200lm LED (216W)	7,100lm LED (51W)	2	PC	WA AG	TC	SQ
	FWH	6-100W A21 (600W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ
JT4218W • W 42" • HT 18" • OAH 96" (OverAll Height)	DZT	35,200lm LED (216W)	12,500lm LED (93W)	2	PC	WA AG	TC	SQ
	FWI	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ
JT5422W • W 54" • HT 22" • OAH 120" (OverAll Height)	DVL	42,200lm LED (260W)	12,500lm LED (93W)	2	PC	WA AG	TC	SQ
	FWJ	12-100W A21 (1200W)	1-100W R40/Par38 (100W)	2	PC	WA AG	TC	SQ

Scale



PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Gallery Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box requires additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19	Medium Base, 60W Max, Incandescent or LED
100W PAR38	Medium Base, 100W Max, Incandescent or LED

Finish Types

PC	Powder Coat
----	-------------

Diffuser Types

WA	Standard Acrylic Diffuser
AG	Premium Glass Diffuser

Mountings

TC	Triple Chain Spreader
----	-----------------------

Louvers

SQ	Square Cell
----	-------------

Dimming Types

0	D1
1	D2
2	D3