

Craft Metal Products Inc.

2751 N. Emerson Ave.
Indianapolis, IN 46218
(800) 669-3254
(317) 545-3252

# Lafayette Series Short Pendant







| Model Number | Lamping Code | Body Lamping | Circuit | Finish | Diffuser | Mounting | Louver |
|---|---|---|---|---|---|---|---|
| **LF1207P**<br>• W 12<br>• HT 10<br>• OAH 48<br>(OverAll Height) | ABL | 2-100W A21 (200W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| **LF1408P**<br>• W 14<br>• HT 13<br>• OAH 48<br>(OverAll Height) | GGP | 5,400lm LED (33W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| | ABN | 3-100W A21 (300W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| **LF1609P**<br>• W 16<br>• HT 14<br>• OAH 48<br>(OverAll Height) | GGS | 5,400lm LED (33W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| | ABP | 3-100W A21 (300W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| **LF1610P**<br>• W 16<br>• HT 14<br>• OAH 48<br>(OverAll Height) | GKP | 5,400lm LED (33W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| | GKO | 3-100W A21 (300W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| **LF1811P**<br>• W 18<br>• HT 17<br>• OAH 48<br>(OverAll Height) | GGT | 5,400lm LED (33W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| | ABR | 3-100W A21 (300W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |
| **LF2208P**<br>• W 22<br>• HT 13 | ENE | 9,700lm LED (58W) | 1 | PC | WA<br>AG | ST<br>CH<br>SM<br>SP | SQ |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| • OAH 48 (OverAll Height) | ENF | 15,800lm LED (116W) | 1 | PC | WA AG | ST CH SM SP | SQ |
| | GIT | 6-60W A19 (360W) | 1 | PC | WA AG | ST CH SM SP | SQ |

SAMPLE CATALOG NUMBER

**Model Number - Lamping Code - Finish - Mounting - Diffuser - Options**

## Scale




**PRODUCT FEATURES**

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin - contact us for alternate color temperature availability
- Standard LED CRI is 80 - contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available - consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH - Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

## Abbreviation Key

### Lamps

| | |
|---|---|
| 100W A21 | Medium Base, 100W Max, Incandesent or LED |
| 60W A19 | Medium Base, 60W Max, Incandesent or LED |

### Finish Types

| | |
|---|---|
| PC | Powder Coat |

### Diffuser Types

| | |
|---|---|
| WA | Standard Acrylic Diffuser |
| AG | Premium Glass Diffuser |

### Mountings

| | |
|---|---|
| ST | Stem |
| CH | Chain |
| SM | Surface Mount Chain |
| SP | Steep Pitch Canopy for Stem |

### Louvers

| | |
|---|---|
| SQ | Square Cell |

### Dimming Types

| | |
|---|---|
| 0 | D1 |
| 1 | D2 |
| 2 | D3 |