
Craft Metal Products Inc.

Lakeland Series Pendant



Model Number	Lamping Code	Body Lamping	Down Lamping	Circuit	Finish	Diffuser	Mounting	Louver
• W 11	GBK	4-60W A19 (240W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SP	SQ

• W 13 • HT 28	DVD	14,500lm LED (86W)	5,100lm LED(36W)	2	PC	WA	ST CH SP	SQ
• OAH 96 (OverAll Height)	DNY	14,500lm LED (86W)	7,100lm LED (51W)	2	PC	WA	ST CH SP	SQ
	DNZ	14,500lm LED(86W)	12,500lm LED (93W)	2	PC	WA	ST CH SP	SQ
	DOA	23,100lm LED (146W)	7,100lm LED (51W)	2	PC	WA	ST CH SP	SQ
	ETG	23,100lm LED (146W)	10,400Im LED (76W)	2	РС	WA	ST CH SP	SQ
	DOB	23,100lm LED (146W)	12,500lm LED (93W)	2	РС	WA	ST CH SP	SQ
	FIY	6-60W A19 (360W)	1-100W PAR38 (100W)	2	РС	WA	ST CH SP	SQ
LK1231L • W 13 • HT 33 • OAH 96 (OverAll Height)	DXL	14,500lm LED (86W)	7,100lm LED (51W)	2	РС	WA	ST CH SP	SQ
	DOS	14,500lm LED (86W)	12,500lm LED (93W)	2	PC	WA	ST CH SP	SQ
	DMF	23,100lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SP	SQ
	DKO	29,500lm LED (192W)	12,500lm LED (93W)	2	PC	WA	ST CH SP	SQ
	FIZ	6-60W A19 (360W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SP	SQ
K1236L • W 13 • HT 39	GKG	10,800lm LED (60W)		1	PC	WA	ST CH SP	SQ
OAH 96 (OverAll Height)	GDZ	15,400lm LED(86W)	5,100lm LED (36W)	2	PC	WA	ST CH SP	SQ
	GEF	17,800lm LED (100W)	12,500lm LED (93W)	2	PC	WA	ST CH SP	SQ
	GES	24,900lm LED (146W)	12,500lm LED (93W)	2	PC	WA	ST CH SP	SQ
	GEV	39,000lm LED (267W)	12,500lm LED (93W)	2	PC	WA	ST CH SP	SQ
	GIX	9-60W A19 (540W)	1-100W PAR38 (100W)	2	PC	WA	ST CH SP	SQ

CEILING HEIGHT: 15' DOOR HEIGHT: 7 SILHOUETTE HEIGHT: 6'

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white acrylic cylinder diffuser (Standard)
- Optional specialty diffuser materials available
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
 Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability • Incandescent lamping is Triac or ELV dimmable - consult lamp and dimmer
- manufacturer for compatibility. Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)For slopes greater than 35 degrees (from horizontal) order steep pitch adapter
- (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

60W A19	Medium Base, 60W Max, Incandesent or LED
100W PAR38	Medium Base, 100W Max, Incandesent or LED

Finish Types	
РС	Powder Coat
Diffuser Type	S
WA	Standard Acrylic Diffuser
Mountings	
ST	Stem

51	Stem
СН	Chain
SP	Steep Pitch Canopy for Stem

Louvers		
SQ	Square Cell	
Dimming	g Types	
0	D1	
1	D2	
2	D3	