Lynnfield Series Pendant



Model Number	Lamping Code	Body Lamping	Circuit	Finish	Diffuser	Mounting
• W 10" • HT 6" • OAH 24" (OverAll Height)	FGT	3,000lm LED (19W)	1	PC	AG	ST CH SM SP
LN1609L	EYU	3,000lm LED (19W)	1	PC	AG	ST CH
• W 16" • HT 9"						SM SP
• OAH 24" (OverAll Height)	EYV	5,100lm LED (33W)	1	PC	AG	ST CH SM SP
	EYW	7,100lm LED (47W)	1	PC	AG	ST CH SM SP
	EYT	1-100W A21 (100W)	1	PC	AG	ST CH SM SP
• W 18" • HT 12" • OAH 24" (OverAll Height)	FBK	3,000lm LED (19W)	1	PC	AG	ST CH SM SP
	FBJ	5,100lm LED (33W)	1	PC	AG	ST CH SM SP
	FBI	7,100lm LED (47W)	1	PC	AG	ST CH SM SP
	GGC	1-100W A21 (100W)	1	PC	AG	ST CH SM SP

PRODUCT FEATURES

- Fabricated and welded metal housing
- Powder coated metallic finish
- UV stable, white glass diffuser (Standard)
- Energy efficient LED lamping
- High power factor electronic LED driver
- Wired for dual circuit operation, Body Lamping and Down Lamping
- Standard LED CCT is 3000 Kelvin contact us for alternate color temperature availability
- Standard LED CRI is 80 contact us for alternate CRI availability
- Incandescent lamping is Triac or ELV dimmable consult lamp and dimmer manufacturer for compatibility.
- Standard LED dimming is 0-10v
- Optional line voltage (Triac or ELV) LED dimming is available consult for compatibility
- Fixture is Chain or Stem hung (extra length may be added, specify OAH) (OAH -Over All Height - is the length from the ceiling to the bottom of the fixture.)
- Mounts to standard electrical junction box (by others), Box may require additional structural support (by others)
- For slopes greater than 35 degrees (from horizontal) order steep pitch adapter (Stem only)
- UL / cUL or ETL / cETL listed
- Contact Us for more lamping options.

Abbreviation Key

Lamps

100W A21 Medium Base, 100W Max, Incandesent or LED

Finish Types

PC Powder Coat

Diffuser Types

AG Premium Glass Diffuser

Mountings

ST Stem
CH Chain

SM Surface Mount Chain

SP Steep Pitch Canopy for Stem

Dimming Types

0 D1 1 D2